



FLUORESCENT MIRROR

CAT. 2 (LOW GLARE LUMINAIRE) CIBSE CATEGORIES 2 SERIES FLUORESCENT LUMINAIRE



Lamella Profile:

(Double Parabolic Lamella End Back Close Louvre)
Extra output Ratio Lamella 20%. Compare with
Lamella Profile-9



Louvre:

High quality attractive glare control aluminium louvre where
provide the most precise lighting for brightness control. It
is an CIBSE LG 3 Cat.2 compliance.

Mainly application:

For I.T. room, conferences room, commercial building.



High quality attractive glare control aluminium louvre where
provide the most precise lighting for brightness control. It
is an CIBSE LG 3 Cat.2 compliance.

Mainly application:


For I.T. room, conferences room, commercial building.



Lamella Profile

Double Parabolic Lamella

Lamella Profile - 7




High quality attractive glare control aluminium louvre where
provide the most precise lighting for brightness control. It
is an CIBSE LG 3 Cat.2 compliance.

Mainly application:


For I.T. room, conferences room, commercial building.



CAT. 2 (LOW GLARE LUMINAIRE) 16 CELLS COMPACT FLUORESCENT LUMINAIRE



PLL 236/R/CAT2 PHOTOMETRIC DISTRIBUTION DIAGRAM LSA 7272A



PLL 336/R/CAT2 PHOTOMETRIC DISTRIBUTION DIAGRAM LSA 6888


Features:

- A special design to give a non glare and low reflection illumination of workplace.
- Provide a well balanced and even light distribution for more comfortable working environment.
- Strong sheet steel housing that is stove enameled inside and outside.
- Louvre are secured with V-clip or hinges to facilitate the change of lamp.
- Innovative lamellas and reflector for improved optical control.
- Easy installation with superior speed mounting system without using any specialize tool.
- Housing are made with 0.5mm high quality cold rolled sheet and treated with epoxy powder coated to give a smooth and attractive finishing.

• GEAR OPTIONAL:

Fitting can be supplied with:

- (a) 6WLL - Extra Low Loss Ballast
- (b) EB - Electronic Ballast
- (c) DEB - Dimmable Electronic Ballast
- (d) PP - Emergency Power Pack



Application:

- Conference room
- Commercial building
- Office
- Bank
- I.T room

Standard Complied:

- MS IEC 60598-2-2 : 1998
- MS IEC 598-1 : 1997
- CIBSE LG 3
- CE



Emergency Power Pack

DIMENSION OF HOUSING

	METRIC SIZE	IMPERIAL SIZE
W	597mm	W 2'
W1	575mm	W1 22" 5/8
L	597mm	L 2'
L1	575mm	L1 22" 5/8
H	135mm	H 5" 1/2
H1	127mm	H1 5"

CIBSE Categories 2 Series Mirror Luminances

MODEL	LAMPS TYPE & RATING	LAMP HOLDER	WEIGHT (KG)	PERFORMANCE SUMMARY				
				LIGHT OUTPUT RATIO	LUMINAIRE POWER	SHR NOMINAL	SHR MAXIMUM	REPORT NO.
PLL 236/R/CAT2	TC-L 2 X 18W	2G11	7.62	61.2 %	80.1 W	0.75	0.87	LSA 7272A
PLL 336/R/CAT2	TC-L 3 X 18W	2G11	8.60	61.7 %	119.0 W	1.25	1.27	LSA 6688